

# DJM LIVE series



The Best Clarity of Sound



## DJM LIVE series

### Technical specification

Description	: 2-way, full range
Operating Mode	: Passive
Frequency Response (-3db)	: 120-20000 Hz
Operating Range (-10db)	: 85-20000 Hz
Components	: LF 2 X 4 inch : HF 1 X 1 inch
Crossover Frequency	: 4500 Hz
Nominal Dispersion (4)	: 100X 50
Nominal Impedance	: 8 ohms
Sensitivity (1)	: 89db @1W/1m (free-space)
Maksimum Input (2)	: 28V (RMS), 100W (con't), 400W (peak)
Maksimum Output (3)	: 109db (Free-Space)
DSP Recommendation	: High Pass Filter 100Hz, 12db/oct
Amplifier Recommendation	: 100W (con't) - 200W (con't) @8 ohms
Dimension	: 390mm(h) X 140mm(w,front) X 70mm(w,back) X 170mm(d)
Weight	: 4.3 kg
Finish	: Doff coating
Enclosure	: Wooden pallet


### Note

- One meter referenced output using 1W pink Noise
- Determined using pink noise 6 dB (CF) at Maximum input for 8 continuous hours
- Measured using pink noise 6 dB (CF) with recommended high pass filter, 100 Hz 12 Db/oct low pass filter and calculated to 1m.
- 2000-10000 Hz Average, 4m measurement distance

musik  
messe



supported by



Musikmesse - Europe's biggest trade fair for the music industry  
Frankfurt 2 to 5 April 2019

# DJM LIVE series

WAVE PARAMETER



The Best Sound of Clarity

