

SX 1501



The Best Clarity of Sound



SX-1501

Technical specification

Description	: Single 15 inch subwoofer
Operating Mode	: Passive
Frequency Response (-3dB)	: 63-1000Hz
Operating Range (-10dB)	: 47-1000Hz
Components	: LF 1 X 15 inch
Nominal Impedance	: 8 ohms
Sensitivity (1)	: 98 db @ 1W/ 1m (half-space)
Maximum Input (1)	: 45V (RMS), 250W (con't), 1000W (peak)
Maximum Output (3)	: 122 db (half-space)
DSP Recommendation	: High Pass Filter 40Hz, 12db/oct
Amplifier Recommendation	: 250W (con't) – 500W (con't) @8 ohms
Dimension	: 635mm(h) X 500mm(w) X 500mm(d)
Weight	: 23 kg
Finish	: Polyurethane, Powder coated grille
Enclosure	: 15mm Local Multiplex

Enclosure Note

- One meter referenced output using 1W pink Noise.
- Determined using pink noise 6dB (CF) at Maximum input for 8 continuous hours.
- Measured using pink noise 6dB (CF) with recommended high pass filter, 100 Hz 12 Db/oct low pass filter and calculated to 1m.
- 2000-10000 Hz, 4m measurement distance

musik
messe

supported by



Musikmesse – Europe's biggest trade fair for the music industry
Frankfurt 2 to 5 April 2019

SX-1501

WAVE PARAMETER



The Best Sound of Clarity

